




**ISO 668 / GENERAL PURPOSE CONTAINERS - ISO 1496-1**

External Dimensions	Standard 20'		Standard 40'		High Cube 40'	
Length	6.058 m	20'	12.192 m	40'	12.192 m	40'
Width	2.438 m	8'	2.438 m	8'	2.438 m	8'
Height	2.591 m	8' 6"	2.591 m	8' 6"	2.896 m	9' 6"

	22 G1 - STANDARD 20'		42 G1 - STANDARD 40'		45 G1 - HIGHT CUBE 40'	
Inside Length	5.898 m	19' 4 13/64 "	12.032 m	39' 5 45/64 "	12.032 m	39' 5 45/64 "
Inside Width	2.352 m	7' 8 19/32 "	2.352 m	7' 8 19/32 "	2.352 m	7' 8 19/32 "
Inside Height	2.393 m	7' 10 7/32 "	2.393 m	7' 10 7/32 "	2.698 m	8' 10 7/32 "
Door Width	2.340 m	7' 8 1/8 "	2.340 m	7' 8 1/8 "	2.340 m	7' 8 1/8 "
Door Height	2.280 m	7' 5 49/64 "	2.280 m	7' 5 49/64 "	2.585 m	8' 5 49/64 "
Cubic Capacity	33.20 m <sup>3</sup>	1,172.4 cft	67.70 m <sup>3</sup>	2,390.8 cft	76.40 m <sup>3</sup>	2,698 cft
Tare Weight	2,220 Kgs.	4,894 Lbs.	3,640 Kgs.	8,024 Lbs.	3,840 Kgs.	8,465 Lbs.
Maximum Payload	28,260 Kgs.	62,302 Lbs.	28,860 Kgs.	63,625 Lbs.	28,660 Kgs.	63,184 Lbs.
Maximum Gross	30,480 Kgs.	67,196 Lbs.	32,500 Kgs.	71,650 Lbs.	32,500 Kgs.	71,650 Lbs.

	22 U1 - OPEN TOP 20'		42 U1 - OPEN TOP 40'	
Inside Length	5.902 m	19' 4 23/64 "	12.036 m	39' 5 55/64 "
Inside Width	2.350 m	7' 8 33/64 "	2.350 m	7' 8 33/64 "
Inside Height	2.348 m	7' 8 7/16 "	2.348 m	7' 8 7/16 "
Door Width	2.340 m	7' 8 1/8 "	2.340 m	7' 8 1/8 "
Door Height	2.280 m	7' 5 49/64 "	2.280 m	7' 5 49/64 "
<b>ROOF</b>				
Width between top rails	2.252 m	7' 4 21/32 "	2.232 m	17' 3 7/8 "
Length between top headers	5.674 m	18' 7 25/64 "	11.798 m	38' 8 31/64 "
Length between troughs	5.378 m	17' 7 47/64 "	11.512 m	37' 9 15/64 "
<b>HEADER</b>				
Width between stubs	1.640 m	5' 4 9/16 "	1.940 m	6' 4 3/8 "
Tare Weight	2,300 Kgs.	5,070 Lbs.	3,800 Kgs.	8,377 Lbs.
Maximum Payload	28,180 Kgs.	62,126 Lbs.	26,680 Kgs.	58,819 Lbs.
Maximum Gross	30,480 Kgs.	67,196 Lbs.	30,480 Kgs.	67,196 Lbs.

	<b>22 P3 - FLAT RACK</b> <b>Collapsible 20'</b>		<b>42 P3 - FLAT RACK</b> <b>Collapsible 40'</b>	
	Inside Length	5.96 m	19' 7"	11.65 m
Inside Width	2.40 m	7' 10"	2.37 m	7' 9"
Inside Height	2.29 m	7' 6"	1.96 m	6' 5"
Length between headers	5.85 m	19' 2"	12.06 m	39' 7"
Length between corners	5.42 m	17' 9"	11.66 m	38' 3"
Width between corners	2.06 m	6' 9"	2.22 m	7' 3"
Tare Weight	3,000 Kgs.	6,613 Lbs.	5,250 Kgs.	5,250 Lbs.
Maximum Payload	37,000 Kgs.	81,571 Lbs.	44,650 Kgs.	98,436 Lbs.
Maximum Gross	40,000 Kgs.	88,184 Lbs.	50,000 Kgs.	110,231 Lbs.

	<b>22 R1 REEFER 20'</b>		<b>45 R1 - REEFER High Cube 40'</b>	
	Inside Length	5.456 m	17' 10 51/64 "	11.59 m
Inside Width	2.294 m	7' 6 5/16 "	2.288 m	7' 6 5/64 "
Max. Cargo Height	2.16 m	7' 1 3/64 "	2.40 m	7' 10 31/64 "
Door Width	2.290 m	7' 6 5/32 "	2.290 m	7' 6 5/32 "
Door Height	2.264 m	7' 5 9/64 "	2.569 m	8' 5 9/64 "
Cubic Capacity	28.4 m <sup>3</sup>	1,002.9 cft	67.50 m <sup>3</sup>	2,383.7 cft
Tare Weight	3,940 Kgs.	6,481 Lbs.	4,600 Kgs.	10,141 Lbs.
Maximum Payload	27,540 Kgs.	60,715 Lbs.	29,400 Kgs.	64,815 Lbs.
Maximum Gross	30,480 Kgs.	67,196 Lbs.	34,000 Kgs.	74,957 Lbs.